

# Bona Preserve HD

## Technical data sheet

Professional  
Floor Care



Waterborne, high performance, quick drying lacquer for restoration and continued protection of finished wood flooring. 1-component, ready-to-use formula conveniently applied with a Bona Applicator Pad. Leaves a highly durable and permanent protective film which can withstand extreme wear. Recommended for finished wood and cork floors, including sports surfaces. Available in Extra Matt and Ultra high gloss.

- Super-quick hardness development
- Outstanding scuff resistance
- Excellent adhesion properties

Observe that Bona Preserve HD can only be removed mechanically after application hence it is recommended to start maintenance directly in connection with freshly installed/renovated surfaces when the surface is perfectly clean. Frequency of following maintenance is determined by the level of wear but 1-2 applications per year are usually suitable.

### Technical data

Binding agent:	Polyurethane
Sheen:	Extra matt (10%) and High gloss (90%)
Dilution:	Do not dilute, product is ready-to-use
Drying time:	Approx. 60 minutes (20°C/60% RH)
Application tools:	Bona Applicator Pad
Coverage:	Approx. 30-50 m <sup>2</sup> /litre
Safety:	Unclassified, see safety data sheet for more details.
Cleaning:	Clean tools in soap and water. Dried product needs to be removed mechanically.
Shelf life:	2 years from the date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Package size:	3 x 3.79 litres (1 gallon)

### Preparations

Remove loose dirt with a vacuum or mop. Clean surface according to the degree of soiling using Bona Cleaner. If a more aggressive cleaning is needed, use Bona Deep Clean Solution. **Note that any residual dirt will remain trapped in the coating and cannot be removed afterwards.** Bona Preserve HD is fully compatible with all Bona Waterborne Lacquers. On surfaces that have been in use and/or with unknown history make an adhesion test prior to use. Wax and certain types of polishes may conflict adhesion. Full stripping of the old maintenance coating is in such case necessary. Observe the general and the product-specific health and safety information prior to use.

### Application

1. Shake container thoroughly before use.

**Bona**®

# Bona Preserve HD

## Technical data sheet

Professional  
Floor Care



2. Pour product onto floor and distribute, in a systematic manner, a thin even coat across the entire surface.
3. If required, it is possible to apply a second layer of product after 30-60 minutes. Careful foot traffic is also possible after this time. To achieve a uniform aspect, it is advised to always treat the entire surface.

### Maintenance

Wetcleaning of the floor may be carried out after 3 days. For regular cleaning use Bona Cleaner. The frequency of maintenance applications with Bona Preserve HD is governed by the level of wear. Assess the floor periodically to ensure that the level of maintenance reflects the level of wear.

### Tips

- Keep the applicator flat to the surface, going wall-to-wall. Avoid lifting the applicator repeatedly as this produces bubbles and eventual surface disturbances.
- Do not work into areas starting to dry as this may produce streaking.
- If applying multiple layers of Bona Preserve HD. Do not stress the drying time between coats. Risk of dissolving previous layer.

**Bona**<sup>®</sup>